

Preset #31 [00-1] "Normal-OD"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo:	442ms = 135 bpm	Type: perc	Type: Soft	Level (dB): 3
	Routing:	Serial	Drive: 10	Threshold (dB): -8	
	LvlOut L (dB):	0	Response: 5	Damp (dB): 90	
	LvlOut R (dB):	0	Level (dB): 0	Speed (/s): 200	
	Map Param:	Off			
	Map Min (%)	0			
	Map Med (%)	50			
	Map Max (%)	100			
EQ	MODULATION	PITCH	DELAY	REVERB	
Freq1 (Hz): 53.1	Type: tremolo	Type: detune	Type: clean	Type: hall	
Gain1 (dB): 12	Speed (Hz): 7.50	Voice 1 (cents): 9	Delay (ms): 420	Decay (s): 2.5	
Width1 (oct): 1.4	Tempo: Disabled	Voice 2 (cents): -9	Tempo: 1/4	PreDelay (ms):	
	Depth (%): 70	Delay 1 (ms): 10	Feedback (%): 9	Mix (%): 25	
Freq2 (Hz): 211	Type: Hard	Delay 2 (ms): 12	HiCut (Hz): 12.6k	Size: Large	
Gain2 (dB): -6	Width (%): 61	Mix (%): 25	LoCut (Hz): 50.12	Hi Color: Clear	
Width2 (oct): 1.6	Hi Cut (Hz): Off		Mix (%): 32	Hi Fac: 0	
				Lo Color: Tight	
Freq3 (Hz): 13.3k				Lo Fac: 9	
Gain3 (dB): 5				Room Lvl (dB)	
Width3 (oct): 0.6				Rev Lvl (dB): -	
				Diffuse: 0	
				Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 384ms = 156 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 30

Tone (%): 65

Level (dB): -22

COMPRESSOR

OFF

Type: perc

Drive: 1

Response: 1

Level (dB): -12

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 20.0k

Gain1 (dB): 12

Width1 (oct): 1.6

Freq2 (Hz): 41.0

Gain2 (dB): -12

Width2 (oct): 0.3

Freq3 (Hz): 19.4k

Gain3 (dB): 12

Width3 (oct): 1.6

MODULATION

OFF

Type: phaser

Speed (Hz): .891

Tempo: 1/2D

Depth (%): 68

Range: Low

Feedback (%): 11

Mix (%): 50

PITCH

OFF

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 360

Tempo: Disabled

Feedback (%): 45

HiCut (Hz): Off

LoCut (Hz): Off

Mix (%): 40

REVERB

Type: hall

Decay (s): 1.2

PreDelay (ms):

Mix (%): 14

Size: Medium

Hi Color: Real

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #33 [00-3] "U2 Pride"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo: 581ms = 103 bpm	Type: distortion	Type: sustain	Type: Soft	Level (dB): 3
	Routing: Serial	Gain (dB): 11	Drive: 10	Threshold (dB): -30	
	LvlOut L (dB): 0	Tone (%): 45	Response: 5	Damp (dB): 50	
	LvlOut R (dB): 0	Level (dB): -22	Level (dB): 0	Speed (/s): 100	
	Map Param: Off				
	Map Min (%): 0				
	Map Med (%): 50				
	Map Max (%): 100				
EQ	MODULATION	PITCH	DELAY	REVERB	
Freq1 (Hz): 79.4	Type: flanger	Type: detune	Type: clean	Type: hall	
Gain1 (dB): -12	Speed (Hz): .194	Voice 1 (cents): 9	Delay (ms): 400	Decay (s): 2.5	
Width1 (oct): 0.8	Tempo: Disabled	Voice 2 (cents): -9	Tempo: 1/8D	PreDelay (ms):	
	Depth (%): 31	Delay 1 (ms): 10	Feedback (%): 20	Mix (%): 25	
Freq2 (Hz): 335	Hi Cut (Hz): 15.8k	Delay 2 (ms): 12	HiCut (Hz): 12.6k	Size: Large	
Gain2 (dB): 6	Feedback (%): -68	Mix (%): 25	LoCut (Hz): 50.12	Hi Color: Clear	
Width2 (oct): 1.0	Feedback HiCut (Hz): 10.0k		Mix (%): 43	Hi Fac: 0	
	Delay (ms): 0.1			Lo Color: Tight	
Freq3 (Hz): 1.30k	Mix (%): 50			Lo Fac: 9	
Gain3 (dB): -10				Room Lvl (dB)	
Width3 (oct): 1.0				Rev Lvl (dB): -	
				Diffuse: 0	
				Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #34 [01-1] "Queen 1"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo:	491ms = 122 bpm	Type: perc	Type: Soft	Level (dB): 3
	Routing:	SemiPar	Drive: 10	Threshold (dB): -33	
	LvlOut L (dB):	0	Response: 5	Damp (dB): 90	
	LvlOut R (dB):	0	Level (dB): 0	Speed (/s): 200	
	Map Param:	Off			
	Map Min (%):	0			
	Map Med (%):	50			
		Map Max (%):	100		
EQ	OFF	MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz):	61.3	Type: phaser	Type: intell P	Type: clean	Type: hall
Gain1 (dB):	12	Speed (Hz): .251	Key: A	Delay (ms): 491	Decay (s): 2.0
Width1 (oct):	0.4	Tempo: Disabled	Scale: Aeolian	Tempo: 1/4	PreDelay (ms):
Freq2 (Hz):	2.18k	Depth (%): 90	Voice 1 (degree): +3	Feedback (%): 40	Mix (%): 20
Gain2 (dB):	0	Range: Low	Voice 2 (degree): -3	HiCut (Hz): 12.6k	Size: Medium
Width2 (oct):	0.5	Feedback (%): -90	Level 1 (dB): 0	LoCut (Hz): 50.12	Hi Color: Bright
		Mix (%): 50	Level 2 (dB): 0	Mix (%): 15	Hi Fac: 6
Freq3 (Hz):	5.46k		Pan 1: -50		Lo Color: Light
Gain3 (dB):	3		Pan 2: 50		Lo Fac: 0
Width3 (oct):	0.8		Delay 1 (ms): 20		Room Lvl (dB)
			Delay 2 (ms): 10		Rev Lvl (dB): -
			Mix (%): 25		Diffuse: 10
					Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #35 [01-2] "The count"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo: 491ms = 122 bpm	Type: distortion	Type: advance	Type: Hard	Level (dB): 3
	Routing: Serial	Gain (dB): 30	Threshold (dB): -20	Threshold (dB): -33	
	LvlOut L (dB): 0	Tone (%): 50	Ratio: 1.1:1	Damp (dB): 90	
	LvlOut R (dB): 0	Level (dB): -14	Attack (ms): 50	Speed (/s): 200	
	Map Param: Off		Release (ms): 1.0s		
	Map Min (%): 0		Level (dB): 0		
	Map Med (%): 50				
	Map Max (%): 100				
EQ	MODULATION	PITCH	DELAY	REVERB	
Freq1 (Hz): 61.3	Type: chorus	Type: intell P	Type: dynam	Type: spring	
Gain1 (dB): 12	Speed (Hz): .299	Key: F#	Delay (ms): 450	Decay (s): 3.8	
Width1 (oct): 0.4	Tempo: Disabled	Scale: Mixolyd	Tempo: Disabled	PreDelay (ms):	
	Depth (%): 50	Voice 1 (degree): +3	Feedback (%): 23	Mix (%): 5	
Freq2 (Hz): 2.18k	Hi Cut (Hz): 446.7	Voice 2 (degree): Uniss	HiCut (Hz): Off	Size: Large	
Gain2 (dB): 0	Delay (ms): 0.1	Level 1 (dB): 0	LoCut (Hz): Off	Hi Color: Real	
Width2 (oct): 0.5	Mix (%): 40	Level 2 (dB): -27	Offset (ms): 15	Hi Fac: 3	
		Pan 1: 0	Sense (dB): 0	Lo Color: Real	
Freq3 (Hz): 5.46k		Pan 2: 0	Damp (dB): 12	Lo Fac: -1	
Gain3 (dB): 3		Delay 1 (ms): 20	Release (ms): 200	Room Lvl (dB)	
Width3 (oct): 0.8		Delay 2 (ms): 20	Mix (%): 24	Rev Lvl (dB): 0	
		Mix (%): 50		Diffuse: 10	
				Shape: Square	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 200ms = 300 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: overdrive

Gain (dB): 10

Tone (%): 57

Level (dB): -8

COMPRESSOR

OFF

Type: advance

Threshold (dB): -29

Ratio: 8.0:1

Attack (ms): 10

Release (ms): 300

Level (dB): -5

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 6

EQ

OFF

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

OFF

Type: tremolo

Speed (Hz): 5.16

Tempo: 1/4

Depth (%): 63

Type: Soft

Width (%): 53

Hi Cut (Hz): 5.01k

PITCH

OFF

Type: intell P

Key: E

Scale: Ionian

Voice 1 (degree): +3

Voice 2 (degree): -5

Level 1 (dB): -1

Level 2 (dB): -2

Pan 1: -50

Pan 2: 50

Delay 1 (ms): 70

Delay 2 (ms): 106

Mix (%): 25

DELAY

OFF

Type: analog

Delay (ms): 356

Tempo: 1/4

Clip (dB): 5

Feedback (%): 43

HiCut (Hz): 2.24k

LoCut (Hz): 177.8

Mix (%): 20

REVERB

Type: spring

Decay (s): 2.9

PreDelay (ms):

Mix (%): 20

Size: Medium

Hi Color: Bright

Hi Fac: 6

Lo Color: Light

Lo Fac: 0

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 22

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #37 [02-1] "Streets"

GLOBAL SETTINGS		DRIVE		ON	COMPRESSOR		OFF	NOISE GATE		OFF	BOOST	
Tempo: 491ms = 122 bpm		Type: distortion			Type: advance			Type: Hard			Level (dB): 3	
Routing: Serial		Gain (dB): 25			Threshold (dB): -20			Threshold (dB): -33				
LvIOut L (dB): 0		Tone (%): 51			Ratio: 1.1:1			Damp (dB): 90				
LvIOut R (dB): 0		Level (dB): -17			Attack (ms): 50			Speed (/s): 200				
Map Param: Off					Release (ms): 1.0s							
Map Min (%): 0					Level (dB): 0							
Map Med (%): 50												
Map Max (%): 100												

EQ		OFF	MODULATION		OFF	PITCH		OFF	DELAY		OFF	REVERB		
Freq1 (Hz): 61.3			Type: chorus			Type: octave			Type: clean			Type: hall		
Gain1 (dB): 12			Speed (Hz): 473			Direction: Up			Delay (ms): 368			Decay (s): 2.5		
Width1 (oct): 0.4			Tempo: Disabled			Range (oct): 1			Tempo: 1/8D			PreDelay (ms):		
			Depth (%): 26			Mix (%): 53			Feedback (%): 33			Mix (%): 25		
Freq2 (Hz): 2.18k			Hi Cut (Hz): 15.8k										Size: Large	
Gain2 (dB): 0			Delay (ms): 14.0										Hi Color: Clear	
Width2 (oct): 0.5			Mix (%): 5										Hi Fac: 0	
													Lo Color: Tight	
Freq3 (Hz): 5.46k													Lo Fac: 9	
Gain3 (dB): 3													Room Lvl (dB)	
Width3 (oct): 0.8													Rev Lvl (dB):	
													Diffuse: 0	
													Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #40 [03-1] "GENERIC SUAVE CLEAN TRE"

GLOBAL SETTINGS		DRIVE	ON	COMPRESSOR	OFF	NOISE GATE	OFF	BOOST
Tempo: 548ms = 109 bpm		Type: distortion		Type: advance		Type: Soft		Level (dB): 5
Routing: Serial		Gain (dB): 30		Threshold (dB): -16		Threshold (dB): -47		
LvIOut L (dB): 0		Tone (%): 50		Ratio: 2.0:1		Damp (dB): 90		
LvIOut R (dB): 0		Level (dB): -16		Attack (ms): 7		Speed (/s): 200		
Map Param: Off				Release (ms): 1.0s				
Map Min (%): 0				Level (dB): 0				
Map Med (%): 50								
Map Max (%): 100								

EQ		OFF	MODULATION		OFF	PITCH		OFF	DELAY		OFF	REVERB	
Freq1 (Hz): 100			Type: tremolo			Type: detune			Type: clean			Type: hall	
Gain1 (dB): 2			Speed (Hz): 7.50			Voice 1 (cents): 9			Delay (ms): 420			Decay (s): 2.5	
Width1 (oct): 1.2			Tempo: Disabled			Voice 2 (cents): -9			Tempo: 1/4			PreDelay (ms):	
			Depth (%): 70			Delay 1 (ms): 10			Feedback (%): 9			Mix (%): 25	
Freq2 (Hz): 2.05k			Type: Hard			Delay 2 (ms): 12			HiCut (Hz): 12.6k			Size: Large	
Gain2 (dB): 2			Width (%): 61			Mix (%): 25			LoCut (Hz): 50.12			Hi Color: Clear	
Width2 (oct): 1.1			Hi Cut (Hz): Off						Mix (%): 32			Hi Fac: 0	
												Lo Color: Tight	
Freq3 (Hz): 6.31k												Lo Fac: 9	
Gain3 (dB): 7												Room Lvl (dB)	
Width3 (oct): 1.1												Rev Lvl (dB):	
												Diffuse: 0	
												Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #43 [04-1] "GENERIC FUERTE PHASER"

Global Settings			Drive	On	Compressor		Noise Gate	Off	Boost
Tempo: 548ms = 109 bpm			Type: distortion		Type: advance		Type: Soft		Level (dB): 5
Routing: Serial			Gain (dB): 30		Threshold (dB): -16		Threshold (dB): -47		
Lv/Out L (dB): 0			Tone (%): 50		Ratio: 2.0:1		Damp (dB): 90		
Lv/Out R (dB): 0			Level (dB): -16		Attack (ms): 7		Speed (/s): 200		
Map Param: Off					Release (ms): 1.0s				
Map Min (%): 0					Level (dB): 0				
Map Med (%): 50									
Map Max (%): 100									
EQ	Off	Modulation		Off	Pitch		Delay	Off	Reverb
Freq1 (Hz): 100		Type: phaser			Type: detune		Type: clean		Type: hall
Gain1 (dB): 2		Speed (Hz): 891			Voice 1 (cents): 9		Delay (ms): 420		Decay (s): 2.5
Width1 (oct): 1.2		Tempo: 1/2D			Voice 2 (cents): -9		Tempo: 1/4		PreDelay (ms):
		Depth (%): 68			Delay 1 (ms): 10		Feedback (%): 9		Mix (%): 25
Freq2 (Hz): 2.05k		Range: Low			Delay 2 (ms): 12		HiCut (Hz): 12.6k		Size: Large
Gain2 (dB): 2		Feedback (%): 11			Mix (%): 25		LoCut (Hz): 50.12		Hi Color: Clear
Width2 (oct): 1.1		Mix (%): 50					Mix (%): 32		Hi Fac: 0
									Lo Color: Tight
Freq3 (Hz): 6.31k									Lo Fac: 9
Gain3 (dB): 7									Room Lvl (dB)
Width3 (oct): 1.1									Rev Lvl (dB):
									Diffuse: 0
									Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #46 [05-1] "HEROES LIMPIO CLEAN"

GLOBAL SETTINGS			DRIVE		COMPRESSOR		NOISE GATE		BOOST	
Tempo: 548ms = 109 bpm			Type: distortion		Type: advance		Type: Soft		Level (dB): 5	
Routing: Serial			Gain (dB): 30		Threshold (dB): -16		Threshold (dB): -47			
LvIOut L (dB): 0			Tone (%): 50		Ratio: 2.0:1		Damp (dB): 90			
LvIOut R (dB): 0			Level (dB): -16		Attack (ms): 7		Speed (/s): 200			
Map Param: Off					Release (ms): 1.0s					
Map Min (%): 0					Level (dB): 0					
Map Med (%): 50										
Map Max (%): 100										
EQ			MODULATION		PITCH		DELAY		REVERB	
			Type: chorus		Type: detune		Type: clean		Type: hall	
Freq1 (Hz): 100			Speed (Hz): .299		Voice 1 (cents): 9		Delay (ms): 360		Decay (s): 2.5	
Gain1 (dB): 2			Tempo: Disabled		Voice 2 (cents): -9		Tempo: Disabled		PreDelay (ms):	
Width1 (oct): 1.2			Depth (%): 50		Delay 1 (ms): 10		Feedback (%): 45		Mix (%): 25	
Freq2 (Hz): 2.05k			Hi Cut (Hz): 446.7		Delay 2 (ms): 12		HiCut (Hz): Off		Size: Large	
Gain2 (dB): 2			Delay (ms): 0.1		Mix (%): 25		LoCut (Hz): Off		Hi Color: Clear	
Width2 (oct): 1.1			Mix (%): 40				Mix (%): 40		Hi Fac: 0	
									Lo Color: Tight	
Freq3 (Hz): 6.31k									Lo Fac: 9	
Gain3 (dB): 7									Room Lvl (dB)	
Width3 (oct): 1.1									Rev Lvl (dB):	
									Diffuse: 0	
									Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 548ms = 109 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -16

COMPRESSOR

OFF

Type: advance

Threshold (dB): -16

Ratio: 2.0:1

Attack (ms): 7

Release (ms): 1.0s

Level (dB): 0

NOISE GATE

ON

Type: Soft

Threshold (dB): -8

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 5

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

ON

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 360

Tempo: Disabled

Feedback (%): 45

HiCut (Hz): Off

LoCut (Hz): Off

Mix (%): 40

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 548ms = 109 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -16

COMPRESSOR

OFF

Type: advance

Threshold (dB): -16

Ratio: 2.0:1

Attack (ms): 7

Release (ms): 1.0s

Level (dB): 0

NOISE GATE

ON

Type: Soft

Threshold (dB): -8

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

OFF

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

ON

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #48 [05-3]

"HEROES SOLO DIST"

Preset #50 [06-2] "U2 Pride crunch green"

GLOBAL SETTINGS

Tempo: 581ms = 103 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

Type: distortion

Gain (dB): 11

Tone (%): 45

Level (dB): -22

COMPRESSOR

Type: sustain

Drive: 10

Response: 5

Level (dB): 0

NOISE GATE

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 3

EQ

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

Type: flanger

Speed (Hz): .194

Tempo: Disabled

Depth (%): 31

Hi Cut (Hz): 15.8k

Feedback (%): -68

Feedback HiCut (Hz): 10.0k

Delay (ms): 0.1

Mix (%): 50

PITCH

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

Type: clean

Delay (ms): 400

Tempo: 1/8D

Feedback (%): 20

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 43

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms): 25

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB):

Diffuse: 0

Shape: Round

Send to Nova

Export XML

Export HTML

Save SysEx

Close

Preset #52 [07-1] "LENNY KRAVITZ CLEAN + FLA"

[illegible]

EQ		OFF	MODULATION		OFF	PITCH		OFF	DELAY		OFF	REVERB	
Freq1 (Hz): 100			Type: flanger			Type: detune			Type: clean			Type: hall	
Gain1 (dB): 2			Speed (Hz): .194			Voice 1 (cents): 9			Delay (ms): 420			Decay (s): 2.5	
Width1 (oct): 1.2			Tempo: Disabled			Voice 2 (cents): -9			Tempo: 1/4			PreDelay (ms): 25	
			Depth (%): 31			Delay 1 (ms): 10			Feedback (%): 9			Mix (%): 25	
Freq2 (Hz): 2.05k			Hi Cut (Hz): 15.8k			Delay 2 (ms): 12			HiCut (Hz): 12.6k			Size: Large	
Gain2 (dB): 2			Feedback (%): -68			Mix (%): 25			LoCut (Hz): 50.12			Hi Color: Clear	
Width2 (oct): 1.1			Feedback HiCut (Hz): 10.0k						Mix (%): 32			Hi Fac: 0	
			Delay (ms): 0.1									Lo Color: Tight	
Freq3 (Hz): 6.31k			Mix (%): 50									Lo Fac: 9	
Gain3 (dB): 7												Room Lvl (dB)	
Width3 (oct): 1.1												Rev Lvl (dB)	
												Diffuse: 0	
												Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 548ms = 109 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -16

COMPRESSOR

OFF

Type: advance

Threshold (dB): -16

Ratio: 2.0:1

Attack (ms): 7

Release (ms): 1.0s

Level (dB): 0

NOISE GATE

ON

Type: Soft

Threshold (dB): -8

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

OFF

Type: flanger

Speed (Hz): .194

Tempo: Disabled

Depth (%): 31

Hi Cut (Hz): 15.8k

Feedback (%): -68

Feedback HiCut (Hz): 10.0k

Delay (ms): 0.1

Mix (%): 50

PITCH

OFF

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

ON

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 498ms = 120 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

OFF

Type: advance

Threshold (dB): -40

Ratio: 4.0:1

Attack (ms): 140

Release (ms): 2.0s

Level (dB): 0

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 77

Speed (/s): 200

BOOST

Level (dB): 2

EQ

OFF

Freq1 (Hz): 218

Gain1 (dB): -5

Width1 (oct): 1.6

Freq2 (Hz): 2.05k

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 7.72k

Gain3 (dB): 12

Width3 (oct): 1.6

MODULATION

ON

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: intell P

Key: C

Scale: Aeolian

Voice 1 (degree): +oct

Voice 2 (degree): Uniss

Level 1 (dB): 0

Level 2 (dB): 0

Pan 1: 0

Pan 2: 0

Delay 1 (ms): 10

Delay 2 (ms): 20

Mix (%): 50

DELAY

ON

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #56 [08-2] "SANTANA CRUNCH"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
Tempo: 498ms = 120 bpm Routing: Serial		Type: distortion	Type: advance	Type: Soft	Level (dB): 3
		Gain (dB): 30	Threshold (dB): -40	Threshold (dB): -30	
	LvlOut L (dB): 0	Tone (%): 50	Ratio: 4.0:1	Damp (dB): 77	
	LvlOut R (dB): 0	Level (dB): -20	Attack (ms): 140	Speed (/s): 200	
Map Param: Off			Release (ms): 2.0s		
Map Min (%): 0			Level (dB): 0		
Map Med (%): 50					
Map Max (%): 100					

EQ	MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz): 218	Type: chorus	Type: intell P	Type: clean	Type: hall
Gain1 (dB): -5	Speed (Hz): .299	Key: C	Delay (ms): 420	Decay (s): 2.5
Width1 (oct): 1.6	Tempo: Disabled	Scale: Aeolian	Tempo: 1/4	PreDelay (ms):
Freq2 (Hz): 2.05k	Depth (%): 50	Voice 1 (degree): +oct	Feedback (%): 9	Mix (%): 25
Gain2 (dB): -6	Hi Cut (Hz): 446.7	Voice 2 (degree): Uniss	HiCut (Hz): 12.6k	Size: Large
Width2 (oct): 1.6	Delay (ms): 0.1	Level 1 (dB): 0	LoCut (Hz): 50.12	Hi Color: Clear
	Mix (%): 40	Level 2 (dB): 0	Mix (%): 32	Hi Fac: 0
		Pan 1: 0		Lo Color: Tight
Freq3 (Hz): 7.72k		Pan 2: 0		Lo Fac: 9
Gain3 (dB): 12		Delay 1 (ms): 10		Room Lvl (dB)
Width3 (oct): 1.6		Delay 2 (ms): 20		Rev Lvl (dB): -
		Mix (%): 50		Diffuse: 0
				Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 498ms = 120 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

OFF

Type: advance

Threshold (dB): -40

Ratio: 4.0:1

Attack (ms): 140

Release (ms): 2.0s

Level (dB): 0

NOISE GATE

ON

Type: Soft

Threshold (dB): -8

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

OFF

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: intell P

Key: C

Scale: Aeolian

Voice 1 (degree): +oct

Voice 2 (degree): Uniss

Level 1 (dB): 0

Level 2 (dB): 0

Pan 1: 0

Pan 2: 0

Delay 1 (ms): 10

Delay 2 (ms): 20

Mix (%): 50

DELAY

ON

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 541ms = 110 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

OFF

Type: advance

Threshold (dB): -20

Ratio: 2.0:1

Attack (ms): 20

Release (ms): 2.0s

Level (dB): 1

NOISE GATE

OFF

Type: Soft

Threshold (dB): -47

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 10

EQ

OFF

Freq1 (Hz): 61.3

Gain1 (dB): 1

Width1 (oct): 1.6

Freq2 (Hz): 3.25k

Gain2 (dB): 4

Width2 (oct): 1.3

Freq3 (Hz): 6.88k

Gain3 (dB): 2

Width3 (oct): 1.6

MODULATION

OFF

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: intell P

Key: A

Scale: Aeolian

Voice 1 (degree): +3

Voice 2 (degree): -3

Level 1 (dB): 0

Level 2 (dB): 0

Pan 1: -50

Pan 2: 50

Delay 1 (ms): 20

Delay 2 (ms): 10

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #59 [09-2] "QUEEN #1 CRUNCH"

GLOBAL SETTINGS		DRIVE		COMPRESSOR		NOISE GATE		BOOST	
Tempo: 541ms = 110 bpm		Type: distortion		Type: advance		Type: Soft		Level (dB): 10	
Routing: Serial		Gain (dB): 30		Threshold (dB): -20		Threshold (dB): -47			
LvIOut L (dB): 0		Tone (%): 50		Ratio: 2.0:1		Damp (dB): 90			
LvIOut R (dB): 0		Level (dB): -20		Attack (ms): 20		Speed (/s): 200			
Map Param: Off				Release (ms): 2.0s					
Map Min (%): 0				Level (dB): 1					
Map Med (%): 50									
Map Max (%): 100									

EQ		OFF	MODULATION		OFF	PITCH		OFF	DELAY		OFF	REVERB	
Freq1 (Hz): 61.3			Type: chorus			Type: intell P			Type: clean			Type: hall	
Gain1 (dB): 1			Speed (Hz): 299			Key: A			Delay (ms): 420			Decay (s): 2.5	
Width1 (oct): 1.6			Tempo: Disabled			Scale: Aeolian			Tempo: 1/4			PreDelay (ms):	
Freq2 (Hz): 3.25k			Depth (%): 50			Voice 1 (degree): +3			Feedback (%): 9			Mix (%): 25	
Gain2 (dB): 4			Hi Cut (Hz): 446.7			Voice 2 (degree): -3			HiCut (Hz): 12.6k			Size: Large	
Width2 (oct): 1.3			Delay (ms): 0.1			Level 1 (dB): 0			LoCut (Hz): 50.12			Hi Color: Clear	
			Mix (%): 40			Level 2 (dB): 0			Mix (%): 32			Hi Fac: 0	
Freq3 (Hz): 6.88k						Pan 1: -50						Lo Color: Tight	
Gain3 (dB): 2						Pan 2: 50						Lo Fac: 9	
Width3 (oct): 1.6						Delay 1 (ms): 20						Room Lvl (dB)	
						Delay 2 (ms): 10						Rev Lvl (dB):	
						Mix (%): 25						Diffuse: 0	
												Shape: Round	

Close	Save SysEx	Export XML	Export HTML	Send to Nova
-------	------------	------------	-------------	--------------

Save SysEx

Export XML Export HTML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 541ms = 110 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

OFF

Type: advance

Threshold (dB): -20

Ratio: 2.0:1

Attack (ms): 20

Release (ms): 2.0s

Level (dB): 1

NOISE GATE

ON

Type: Soft

Threshold (dB): -8

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 10

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

OFF

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: intell P

Key: A

Scale: Aeolian

Voice 1 (degree): +3

Voice 2 (degree): -3

Level 1 (dB): 0

Level 2 (dB): 0

Pan 1: -50

Pan 2: 50

Delay 1 (ms): 20

Delay 2 (ms): 10

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 541ms = 110 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

OFF

Type: advance

Threshold (dB): -20

Ratio: 2.0:1

Attack (ms): 20

Release (ms): 2.0s

Level (dB): 1

NOISE GATE

OFF

Type: Soft

Threshold (dB): -47

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 10

EQ

OFF

Freq1 (Hz): 61.3

Gain1 (dB): 1

Width1 (oct): 1.6

Freq2 (Hz): 3.25k

Gain2 (dB): 4

Width2 (oct): 1.3

Freq3 (Hz): 6.88k

Gain3 (dB): 2

Width3 (oct): 1.6

MODULATION

OFF

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: intell P

Key: E

Scale: Ionian

Voice 1 (degree): +3

Voice 2 (degree): -5

Level 1 (dB): -1

Level 2 (dB): -2

Pan 1: -50

Pan 2: 50

Delay 1 (ms): 70

Delay 2 (ms): 106

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 541ms = 110 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

Type: advance

Threshold (dB): -20

Ratio: 2.0:1

Attack (ms): 20

Release (ms): 2.0s

Level (dB): 1

NOISE GATE

Type: Soft

Threshold (dB): -47

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 10

EQ

Freq1 (Hz): 61.3

Gain1 (dB): 1

Width1 (oct): 1.6

Freq2 (Hz): 3.25k

Gain2 (dB): 4

Width2 (oct): 1.3

Freq3 (Hz): 6.88k

Gain3 (dB): 2

Width3 (oct): 1.6

MODULATION

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

Type: intell P

Key: E

Scale: Ionian

Voice 1 (degree): +3

Voice 2 (degree): -5

Level 1 (dB): -1

Level 2 (dB): -2

Pan 1: -50

Pan 2: 50

Delay 1 (ms): 70

Delay 2 (ms): 106

Mix (%): 25

DELAY

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #62 [10-2] "QUEEN #2 CRUNCH"

GLOBAL SETTINGS

Tempo: 541ms = 110 bpm

Routing: Serial

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: distortion

Gain (dB): 30

Tone (%): 50

Level (dB): -20

COMPRESSOR

OFF

Type: advance

Threshold (dB): -20

Ratio: 2.0:1

Attack (ms): 20

Release (ms): 2.0s

Level (dB): 1

NOISE GATE

ON

Type: Soft

Threshold (dB): -8

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 10

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

OFF

Type: chorus

Speed (Hz): .299

Tempo: Disabled

Depth (%): 50

Hi Cut (Hz): 446.7

Delay (ms): 0.1

Mix (%): 40

PITCH

OFF

Type: intell P

Key: E

Scale: Ionian

Voice 1 (degree): +3

Voice 2 (degree): -5

Level 1 (dB): -1

Level 2 (dB): -2

Pan 1: -50

Pan 2: 50

Delay 1 (ms): 70

Delay 2 (ms): 106

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #64 [11-1] "Guns'n Roses Clean"

GLOBAL SETTINGS

Tempo: 200ms = 300 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 26

Tone (%): 42

Level (dB): -22

COMPRESSOR

OFF

Type: perc

Drive: 1

Response: 1

Level (dB): -12

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

OFF

Type: phaser

Speed (Hz): .891

Tempo: 1/2D

Depth (%): 68

Range: Low

Feedback (%): 11

Mix (%): 50

PITCH

ON

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):: 25

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB):

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 200ms = 300 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 26

Tone (%): 42

Level (dB): -22

COMPRESSOR

OFF

Type: perc

Drive: 1

Response: 1

Level (dB): -12

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

OFF

Type: phaser

Speed (Hz): .891

Tempo: 1/2D

Depth (%): 68

Range: Low

Feedback (%): 11

Mix (%): 50

PITCH

OFF

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 200ms = 300 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: distortion

Gain (dB): 26

Tone (%): 42

Level (dB): -22

COMPRESSOR

OFF

Type: perc

Drive: 1

Response: 1

Level (dB): -12

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 3

EQ

OFF

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

OFF

Type: phaser

Speed (Hz): .891

Tempo: 1/2D

Depth (%): 68

Range: Low

Feedback (%): 11

Mix (%): 50

PITCH

OFF

Type: detune

Voice 1 (cents): 9

Voice 2 (cents): -9

Delay 1 (ms): 10

Delay 2 (ms): 12

Mix (%): 25

DELAY

OFF

Type: clean

Delay (ms): 420

Tempo: 1/4

Feedback (%): 9

HiCut (Hz): 12.6k

LoCut (Hz): 50.12

Mix (%): 32

REVERB

Type: hall

Decay (s): 2.5

PreDelay (ms):

Mix (%): 25

Size: Large

Hi Color: Clear

Hi Fac: 0

Lo Color: Tight

Lo Fac: 9

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 0

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #67 [12-1] "ALASKA CLEAN"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo: 801ms = 74 bpm	Type: overdrive	Type: advance	Type: Soft	Level (dB): 3
	Routing: Serial	Gain (dB): 10	Threshold (dB): -30	Threshold (dB): -47	
	LvlOut L (dB): 0	Tone (%): 95	Ratio: 2.0:1	Damp (dB): 90	
	LvlOut R (dB): 0	Level (dB): -6	Attack (ms): 20	Speed (/s): 200	
	Map Param: Off		Release (ms): 2.0s		
	Map Min (%): 0		Level (dB): 0		
	Map Med (%): 50				
	Map Max (%): 100				
EQ	MODULATION	PITCH	DELAY	REVERB	
Freq1 (Hz): 10.9k	Type: tremolo	Type: detune	Type: clean	Type: hall	
Gain1 (dB): 3	Speed (Hz): 7.50	Voice 1 (cents): 9	Delay (ms): 420	Decay (s): 2.5	
Width1 (oct): 1.6	Tempo: Disabled	Voice 2 (cents): -9	Tempo: 1/4	PreDelay (ms):	
	Depth (%): 70	Delay 1 (ms): 10	Feedback (%): 9	Mix (%): 25	
Freq2 (Hz): 64.9	Type: Hard	Delay 2 (ms): 12	HiCut (Hz): 12.6k	Size: Large	
Gain2 (dB): -1	Width (%): 61	Mix (%): 25	LoCut (Hz): 50.12	Hi Color: Clear	
Width2 (oct): 0.8	Hi Cut (Hz): Off		Mix (%): 32	Hi Fac: 0	
				Lo Color: Tight	
Freq3 (Hz): Off				Lo Fac: 9	
Gain3 (dB): -4				Room Lvl (dB)	
Width3 (oct): 1.6				Rev Lvl (dB): -	
				Diffuse: 0	
				Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #69 [12-3] "ALASKA LEAD"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo:	801ms = 74 bpm	OFF	ON	
	Routing:	Serial	Type: advance	Type: Soft	Level (dB): 3
	LvlOut L (dB):	0	Threshold (dB): -30	Threshold (dB): -8	
	LvlOut R (dB):	0	Ratio: 2.0:1	Damp (dB): 90	
	Map Param:	Off	Attack (ms): 20	Speed (/s): 200	
	Map Min (%):	0	Release (ms): 2.0s		
	Map Med (%):	50	Level (dB): 0		
		Map Max (%): 100			
EQ	MODULATION	PITCH	DELAY	REVERB	
Freq1 (Hz): 53.1	Type: tremolo	Type: detune	Type: clean	Type: hall	
Gain1 (dB): 12	Speed (Hz): 7.50	Voice 1 (cents): 9	Delay (ms): 420	Decay (s): 2.5	
Width1 (oct): 1.4	Tempo: Disabled	Voice 2 (cents): -9	Tempo: 1/4	PreDelay (ms):	
	Depth (%): 70	Delay 1 (ms): 10	Feedback (%): 9	Mix (%): 25	
Freq2 (Hz): 211	Type: Hard	Delay 2 (ms): 12	HiCut (Hz): 12.6k	Size: Large	
Gain2 (dB): -6	Width (%): 61	Mix (%): 25	LoCut (Hz): 50.12	Hi Color: Clear	
Width2 (oct): 1.6	Hi Cut (Hz): Off		Mix (%): 32	Hi Fac: 0	
				Lo Color: Tight	
Freq3 (Hz): 13.3k				Lo Fac: 9	
Gain3 (dB): 5				Room Lvl (dB)	
Width3 (oct): 0.6				Rev Lvl (dB): -	
				Diffuse: 0	
				Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #70 [13-1] "GENERIC SUAVE CLEAN TR2"

GLOBAL SETTINGS		DRIVE	ON	COMPRESSOR	OFF	NOISE GATE	OFF	BOOST
Tempo: 548ms = 109 bpm		Type: distortion		Type: advance		Type: Soft		Level (dB): 5
Routing: Serial		Gain (dB): 30		Threshold (dB): -16		Threshold (dB): -47		
LvIOut L (dB): 0		Tone (%): 50		Ratio: 2.0:1		Damp (dB): 90		
LvIOut R (dB): 0		Level (dB): -16		Attack (ms): 7		Speed (/s): 200		
Map Param: Off				Release (ms): 1.0s				
Map Min (%): 0				Level (dB): 0				
Map Med (%): 50								
Map Max (%): 100								

EQ		OFF	MODULATION		OFF	PITCH		OFF	DELAY		OFF	REVERB	
Freq1 (Hz): 100			Type: tremolo			Type: detune			Type: clean			Type: hall	
Gain1 (dB): 2			Speed (Hz): 7.50			Voice 1 (cents): 9			Delay (ms): 420			Decay (s): 2.5	
Width1 (oct): 1.2			Tempo: Disabled			Voice 2 (cents): -9			Tempo: 1/4			PreDelay (ms):	
			Depth (%): 70			Delay 1 (ms): 10			Feedback (%): 9			Mix (%): 25	
Freq2 (Hz): 2.05k			Type: Hard			Delay 2 (ms): 12			HiCut (Hz): 12.6k			Size: Large	
Gain2 (dB): 2			Width (%): 61			Mix (%): 25			LoCut (Hz): 50.12			Hi Color: Clear	
Width2 (oct): 1.1			Hi Cut (Hz): Off						Mix (%): 32			Hi Fac: 0	
												Lo Color: Tight	
Freq3 (Hz): 6.31k												Lo Fac: 9	
Gain3 (dB): 7												Room Lvl (dB)	
Width3 (oct): 1.1												Rev Lvl (dB):	
												Diffuse: 0	
												Shape: Round	

Close Save SysEx Export XML Export HTML Send to Nova

Preset #73 [14-1] "STREETS"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
Tempo: 480ms = 125 bpm		Type: overdrive	Type: advance	Type: Soft	Level (dB): 0
Routing: SemiPar		Gain (dB): 6	Threshold (dB): -29	Threshold (dB): -30	
LvIOut L (dB): 0		Tone (%): 30	Ratio: 4.0:1	Damp (dB): 50	
LvIOut R (dB): 0		Level (dB): 0	Attack (ms): 50	Speed (/s): 100	
Map Param: Off			Release (ms): 70		
Map Min (%): 0			Level (dB): -12		
Map Med (%): 50					
Map Max (%): 100					
EQ	OFF	MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz): 79.4		Type: chorus	Type: wham	Type: dual	Type: plate
Gain1 (dB): -12		Speed (Hz): .473	Pitch (%): 0	Delay 1 (ms): 120	Decay (s): 1.5
Width1 (oct): 0.8		Tempo: Disabled	Direction: Up	Delay 2 (ms): 360	PreDelay (ms):
		Depth (%): 26	Range (oct): 2	Tempo 1: 1/4	Mix (%): 16
Freq2 (Hz): 335		Hi Cut (Hz): 15.8k		Tempo 2: 1/8D	Size: Medium
Gain2 (dB): 6		Delay (ms): 14.0		Feedback 1 (%): 7	Hi Color: Warm
Width2 (oct): 1.0		Mix (%): 5		Feedback 2 (%): 30	Hi Fac: 5
				HiCut (Hz): Off	Lo Color: Real
Freq3 (Hz): 1.30k				LoCut (Hz): Off	Lo Fac: 6
Gain3 (dB): -10				Pan 1: 18	Room Lvl (dB)
Width3 (oct): 1.0				Pan 2: -50	Rev Lvl (dB): -
				Mix (%): 46	Diffuse: 23
					Shape: Curved

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 594ms = 101 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: overdrive

Gain (dB): 6

Tone (%): 30

Level (dB): 0

COMPRESSOR

OFF

Type: advance

Threshold (dB): -29

Ratio: 4.0:1

Attack (ms): 50

Release (ms): 70

Level (dB): -12

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 0

EQ

OFF

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

ON

Type: chorus

Speed (Hz): .473

Tempo: Disabled

Depth (%): 26

Hi Cut (Hz): 15.8k

Delay (ms): 14.0

Mix (%): 5

PITCH

OFF

Type: wham

Pitch (%): 0

Direction: Up

Range (oct): 2

DELAY

ON

Type: dual

Delay 1 (ms): 594

Delay 2 (ms): 445

Tempo 1: 1/4

Tempo 2: 1/8D

Feedback 1 (%): 7

Feedback 2 (%): 35

HiCut (Hz): Off

LoCut (Hz): Off

Pan 1: 24

Pan 2: -50

Mix (%): 46

REVERB

Type: plate

Decay (s): 1.5

PreDelay (ms):

Mix (%): 16

Size: Medium

Hi Color: Warm

Hi Fac: 5

Lo Color: Real

Lo Fac: 6

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 23

Shape: Curved

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #74 [14-2] "STILL HAVENTFOUND"

Preset #75 [14-3] "PRIDE"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo:	571ms = 105 bpm	Type: overdrive	Type: Soft	Level (dB): 0
	Routing:	SemiPar	Gain (dB): 6	Threshold (dB): -30	
	LvlOut L (dB):	0	Tone (%): 30	Damp (dB): 50	
	LvlOut R (dB):	0	Level (dB): 0	Speed (/s): 100	
	Map Param:	Off	Release (ms): 70		
	Map Min (%):	0	Level (dB): -12		
	Map Med (%):	50			
		Map Max (%):	100		
EQ	OFF	MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz):	79.4	Type: chorus	Type: wham	Type: dual	Type: plate
Gain1 (dB):	-12	Speed (Hz): .708	Pitch (%): 0	Delay 1 (ms): 571	Decay (s): 1.5
Width1 (oct):	0.8	Tempo: Disabled	Direction: Up	Delay 2 (ms): 428	PreDelay (ms):
		Depth (%): 24	Range (oct): 2	Tempo 1: 1/4	Mix (%): 16
Freq2 (Hz):	335	Hi Cut (Hz): 15.8k		Tempo 2: 1/8D	Size: Medium
Gain2 (dB):	6	Delay (ms): 14.0		Feedback 1 (%): 8	Hi Color: Warm
Width2 (oct):	1.0	Mix (%): 6		Feedback 2 (%): 21	Hi Fac: 5
				HiCut (Hz): Off	Lo Color: Real
Freq3 (Hz):	1.30k			LoCut (Hz): Off	Lo Fac: 6
Gain3 (dB):	-10			Pan 1: 31	Room Lvl (dB)
Width3 (oct):	1.0			Pan 2: -50	Rev Lvl (dB): -
				Mix (%): 40	Diffuse: 23
					Shape: Curved

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #76 [15-1] "WITHOUT YOU"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo: 545ms = 110 bpm	Type: overdrive	Type: advance	Type: Soft	Level (dB): 0
	Routing: SemiPar	Gain (dB): 6	Threshold (dB): -29	Threshold (dB): -30	
	LvlOut L (dB): 0	Tone (%): 30	Ratio: 4.0:1	Damp (dB): 50	
	LvlOut R (dB): 0	Level (dB): 0	Attack (ms): 50	Speed (/s): 100	
	Map Param: Off		Release (ms): 70		
	Map Min (%): 0		Level (dB): -12		
	Map Med (%): 50				
		Map Max (%): 100			
EQ		MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz): 79.4		Type: chorus	Type: wham	Type: dual	Type: plate
Gain1 (dB): -12		Speed (Hz): .473	Pitch (%): 0	Delay 1 (ms): 545	Decay (s): 1.5
Width1 (oct): 0.8		Tempo: Disabled	Direction: Up	Delay 2 (ms): 408	PreDelay (ms):
		Depth (%): 26	Range (oct): 2	Tempo 1: 1/4	Mix (%): 16
Freq2 (Hz): 335		Hi Cut (Hz): 15.8k		Tempo 2: 1/8D	Size: Medium
Gain2 (dB): 6		Delay (ms): 14.0		Feedback 1 (%): 0	Hi Color: Warm
Width2 (oct): 1.0		Mix (%): 5		Feedback 2 (%): 7	Hi Fac: 5
				HiCut (Hz): Off	Lo Color: Real
Freq3 (Hz): 1.30k				LoCut (Hz): Off	Lo Fac: 6
Gain3 (dB): -10				Pan 1: 15	Room Lvl (dB)
Width3 (oct): 1.0				Pan 2: -50	Rev Lvl (dB): -
				Mix (%): 29	Diffuse: 23
					Shape: Curved

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #77 [15-2] "COMFORTABLY SOLO"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
	Tempo: 970ms = 61 bpm	Type: overdrive	Type: advance	Type: Soft	Level (dB): 0
	Routing: SemiPar	Gain (dB): 6	Threshold (dB): -29	Threshold (dB): -30	
	LvlOut L (dB): 0	Tone (%): 30	Ratio: 4.0:1	Damp (dB): 50	
	LvlOut R (dB): 0	Level (dB): 0	Attack (ms): 50	Speed (/s): 100	
	Map Param: Off		Release (ms): 70		
	Map Min (%): 0		Level (dB): -12		
	Map Med (%): 50				
		Map Max (%): 100			
EQ	OFF	MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz): 79.4	Type: phaser	Type: wham	Type: clean	Type: plate	Type: plate
Gain1 (dB): -12	Speed (Hz): 1.15	Pitch (%): 0	Delay (ms): 485	Decay (s): 1.5	Decay (s): 1.5
Width1 (oct): 0.8	Tempo: Disabled	Direction: Up	Tempo: 1/8	PreDelay (ms):	PreDelay (ms):
	Depth (%): 90	Range (oct): 2	Feedback (%): 25	Mix (%): 16	Mix (%): 16
Freq2 (Hz): 335	Range: Low		HiCut (Hz): Off	Size: Medium	Size: Medium
Gain2 (dB): 6	Feedback (%): 0		LoCut (Hz): Off	Hi Color: Warm	Hi Color: Warm
Width2 (oct): 1.0	Mix (%): 38		Mix (%): 22	Hi Fac: 5	Hi Fac: 5
				Lo Color: Real	Lo Color: Real
Freq3 (Hz): 1.30k				Lo Fac: 6	Lo Fac: 6
Gain3 (dB): -10				Room Lvl (dB)	Room Lvl (dB)
Width3 (oct): 1.0				Rev Lvl (dB): -	Rev Lvl (dB): -
				Diffuse: 23	Diffuse: 23
				Shape: Curved	Shape: Curved

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 970ms = 61 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

ON

Type: overdrive

Gain (dB): 6

Tone (%): 30

Level (dB): 0

COMPRESSOR

OFF

Type: advance

Threshold (dB): -29

Ratio: 4.0:1

Attack (ms): 50

Release (ms): 70

Level (dB): -12

NOISE GATE

OFF

Type: Soft

Threshold (dB): -30

Damp (dB): 50

Speed (/s): 100

BOOST

Level (dB): 0

EQ

OFF

Freq1 (Hz): 79.4

Gain1 (dB): -12

Width1 (oct): 0.8

Freq2 (Hz): 335

Gain2 (dB): 6

Width2 (oct): 1.0

Freq3 (Hz): 1.30k

Gain3 (dB): -10

Width3 (oct): 1.0

MODULATION

OFF

Type: phaser

Speed (Hz): 1.15

Tempo: Disabled

Depth (%): 90

Range: Low

Feedback (%): 0

Mix (%): 38

PITCH

OFF

Type: wham

Pitch (%): 0

Direction: Up

Range (oct): 2

DELAY

ON

Type: clean

Delay (ms): 485

Tempo: 1/8

Feedback (%): 25

HiCut (Hz): Off

LoCut (Hz): Off

Mix (%): 22

REVERB

Type: plate

Decay (s): 1.5

PreDelay (ms):

Mix (%): 16

Size: Medium

Hi Color: Warm

Hi Fac: 5

Lo Color: Real

Lo Fac: 6

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 23

Shape: Curved

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #79 [16-1] "MAIN MONEY"

GLOBAL SETTINGS		DRIVE	COMPRESSOR	NOISE GATE	BOOST
Tempo: 544ms = 110 bpm		Type: overdrive	Type: advance	Type: Hard	Level (dB): 0
Routing: SemiPar		Gain (dB): 14	Threshold (dB): -40	Threshold (dB): -40	
LvIOut L (dB): 0		Tone (%): 0	Ratio: 1.8:1	Damp (dB): 90	
LvIOut R (dB): 0		Level (dB): 0	Attack (ms): 140	Speed (/s): 200	
Map Param: Off			Release (ms): 2.0s		
Map Min (%): 0			Level (dB): -7		
Map Med (%): 50					
Map Max (%): 100					

EQ	MODULATION	PITCH	DELAY	REVERB
Freq1 (Hz): 53.1	Type: tremolo	Type: wham	Type: clean	Type: spring
Gain1 (dB): 12	Speed (Hz): 11.22	Pitch (%): 0	Delay (ms): 544	Decay (s): 2.0
Width1 (oct): 1.4	Tempo: 1/16T	Direction: Up	Tempo: 1/4	PreDelay (ms):
	Depth (%): 77	Range (oct): 1	Feedback (%): 35	Mix (%): 20
Freq2 (Hz): 211	Type: Hard		HiCut (Hz): Off	Size: Medium
Gain2 (dB): -6	Width (%): 33		LoCut (Hz): Off	Hi Color: Bright
Width2 (oct): 1.6	Hi Cut (Hz): 14.1k		Mix (%): 18	Hi Fac: 6
				Lo Color: Light
Freq3 (Hz): 13.3k				Lo Fac: 0
Gain3 (dB): 5				Room Lvl (dB)
Width3 (oct): 0.6				Rev Lvl (dB): -
				Diffuse: 10
				Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova

Preset #80 [16-2] "MAIN MONEY 2"

GLOBAL SETTINGS			DRIVE		COMPRESSOR		NOISE GATE		BOOST	
Tempo: 544ms = 110 bpm			Type: overdrive		Type: advance		Type: Hard		Level (dB): 0	
Routing: SemiPar			Gain (dB): 14		Threshold (dB): -40		Threshold (dB): -40			
LvIOut L (dB): 0			Tone (%): 0		Ratio: 1.8:1		Damp (dB): 90			
LvIOut R (dB): 0			Level (dB): 0		Attack (ms): 140		Speed (/s): 200			
Map Param: Off					Release (ms): 2.0s					
Map Min (%): 0					Level (dB): -7					
Map Med (%): 50										
Map Max (%): 100										
EQ			MODULATION		PITCH		DELAY		REVERB	
			Type: tremolo		Type: wham		Type: clean		Type: spring	
Freq1 (Hz): 53.1			Speed (Hz): 11.22		Pitch (%): 0		Delay (ms): 544		Decay (s): 2.0	
Gain1 (dB): 12			Tempo: 1/16T		Direction: Up		Tempo: 1/4		PreDelay (ms): 20	
Width1 (oct): 1.4			Depth (%): 77		Range (oct): 1		Feedback (%): 35		Mix (%) : 20	
Freq2 (Hz): 211			Type: Hard				HiCut (Hz): Off		Size: Medium	
Gain2 (dB): -6			Width (%): 33				LoCut (Hz): Off		Hi Color: Bright	
Width2 (oct): 1.6			Hi Cut (Hz): 14.1k				Mix (%) : 18		Hi Fac: 6	
									Lo Color: Light	
Freq3 (Hz): 13.3k									Lo Fac: 0	
Gain3 (dB): 5									Room Lvl (dB)	
Width3 (oct): 0.6									Rev Lvl (dB):	
									Diffuse: 10	
									Shape: Round	

Close

Save SysEx

Export XML

Export HTML

Send to Nova

GLOBAL SETTINGS

Tempo: 544ms = 110 bpm

Routing: SemiPar

LvlOut L (dB): 0

LvlOut R (dB): 0

Map Param: Off

Map Min (%): 0

Map Med (%): 50

Map Max (%): 100

DRIVE

OFF

Type: overdrive

Gain (dB): 14

Tone (%): 0

Level (dB): 0

COMPRESSOR

OFF

Type: advance

Threshold (dB): -40

Ratio: 1.8:1

Attack (ms): 140

Release (ms): 2.0s

Level (dB): -7

NOISE GATE

OFF

Type: Hard

Threshold (dB): -40

Damp (dB): 90

Speed (/s): 200

BOOST

Level (dB): 0

EQ

OFF

Freq1 (Hz): 53.1

Gain1 (dB): 12

Width1 (oct): 1.4

Freq2 (Hz): 211

Gain2 (dB): -6

Width2 (oct): 1.6

Freq3 (Hz): 13.3k

Gain3 (dB): 5

Width3 (oct): 0.6

MODULATION

OFF

Type: tremolo

Speed (Hz): 11.22

Tempo: 1/16T

Depth (%): 77

Type: Hard

Width (%): 33

Hi Cut (Hz): 14.1k

PITCH

OFF

Type: wham

Pitch (%): 0

Direction: Up

Range (oct): 1

DELAY

OFF

Type: clean

Delay (ms): 544

Tempo: 1/4

Feedback (%): 35

HiCut (Hz): Off

LoCut (Hz): Off

Mix (%): 18

REVERB

Type: spring

Decay (s): 2.0

PreDelay (ms):

Mix (%): 20

Size: Medium

Hi Color: Bright

Hi Fac: 6

Lo Color: Light

Lo Fac: 0

Room Lvl (dB)

Rev Lvl (dB): -

Diffuse: 10

Shape: Round

Close

Save SysEx

Export XML

Export HTML

Send to Nova